

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 1 / 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. product identifiers**

Article No. (manufacturer/supplier) 243X46  
Trade name/designation PREMIUM Window Pen  
Art.no. 243246, 243546  
all colours, all gloss values

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

Coating (Paint, Varnish).

**Uses advised against:**

Do not use for products which come into contact with the food stuffs.

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer/supplier**

Heinrich König GmbH & Co.KG  
An der Rosenhelle 5  
D-61138 Niederdorfelden

Telephone: +49 6101 5360 0  
Telefax: +49 6101 5360 11  
E-mail: [Info@heinrich-koenig.de](mailto:Info@heinrich-koenig.de)  
Website: [www.heinrich-koenig.de](http://www.heinrich-koenig.de)

**Department responsible for information:**

Laboratory

Only available during office hours:

Telephone: +49 6101 5360 71  
Mon - Thurs 08:00 to 16:00  
Friday 08:00 - 12:30

E-mail (competent person)

[SDB@heinrich-koenig.de](mailto:SDB@heinrich-koenig.de)

**1.4. Emergency telephone number**

Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK  
GmbH +49 (0)6132-84463

Ireland (Éireann)

Emergency medical information: 8am-10pm (seven days)  
contact National Poisons Information Centre, Beaumont  
Hospital, Dublin 9 DOV2NO, Ireland.  
Telephone Number: "+353 (0)1 809 2166 "

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

STOT SE 3 / H336

STOT-single exposure

May cause drowsiness or dizziness.

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Danger**

**Hazard statements**

H225

Highly flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

**Precautionary statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370 + P378

In case of fire: Use foam to extinguish.

P403 + P235

Store in a well-ventilated place. Keep cool.

**Hazard components for labelling**

1-methoxy-2-propanol

**Supplemental hazard information**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 2 / 13

EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition / information on ingredients**

**3.2. Mixtures**

**Description** Acrylic resin lacquer

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
203-539-1 107-98-2 603-064-00-3	01-2119457435-35-xxxx 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	20 < 25
204-658-1 123-86-4 607-025-00-1	01-2119485493-29-xxxx n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	10 < 20
203-603-9 108-65-6 607-195-00-7	01-2119475791-29-xxxx 2-methoxy-1-methylethyl acetate STOT SE 3 H336 / Flam. Liq. 3 H226	7 < 10
201-159-0 78-93-3 606-002-00-3	01-2119457290-43-xxxx butanone Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	5 < 7
905-588-0	01-2119488216-32-xxxx Reaction mass of ethylbenzene and xylene Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226 Specific concentration limit (SCL): STOT RE 2 H373 >= 10	2,5 < 3

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 3 / 13

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

**6.4. Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**7.3. Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

\*

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 4 / 13

**Occupational exposure limit values:**

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

TWA: 375 mg/m<sup>3</sup>; 100 ppm

STEL: 560 mg/m<sup>3</sup>; 150 ppm

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

TWA: 724 mg/m<sup>3</sup>; 150 ppm

STEL: 966 mg/m<sup>3</sup>; 200 ppm

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

TWA: 274 mg/m<sup>3</sup>; 50 ppm

STEL: 548 mg/m<sup>3</sup>; 100 ppm

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

TWA: 600 mg/m<sup>3</sup>; 200 ppm

STEL: 899 mg/m<sup>3</sup>; 300 ppm

Reaction mass of ethylbenzene and xylene

EC No. 905-588-0

TWA: 220 mg/m<sup>3</sup>; 50 ppm

STEL: 441 mg/m<sup>3</sup>; 100 ppm

**Additional information**

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

**DNEL:**

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 183 mg/kg

DNEL acute inhalative (local), Workers: 553,5 mg/m<sup>3</sup>

DNEL acute inhalative (systemic), Workers: 553,5 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 369 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 33 mg/kg

DNEL long-term dermal (systemic), Consumer: 78 mg/kg

DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m<sup>3</sup>

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

DNEL long-term dermal (systemic), Workers: 1161 mg/kg

DNEL long-term inhalative (systemic), Workers: 600 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 31 mg/kg

DNEL acute dermal, short-term (local), Consumer: 412 mg/kg

DNEL long-term dermal (systemic), Consumer: 206 mg/kg

DNEL long-term inhalative (systemic), Consumer: 106 mg/m<sup>3</sup>

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute dermal, short-term (systemic), Workers: 11 mg/kg

DNEL long-term dermal (systemic), Workers: 7 mg/kg

DNEL acute inhalative (local), Workers: 600 mg/m<sup>3</sup>

DNEL acute inhalative (systemic), Workers: 600 mg/m<sup>3</sup>

DNEL long-term inhalative (local), Workers: 300 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 48 mg/m<sup>3</sup>

DNEL short-term oral (acute), Consumer: 2 mg/kg

DNEL long-term oral (repeated), Consumer: 2 mg/kg

DNEL acute dermal, short-term (systemic), Consumer: 6 mg/kg

DNEL long-term dermal (systemic), Consumer: 3,4 mg/kg

DNEL acute inhalative (local), Consumer: 300 mg/m<sup>3</sup>

DNEL acute inhalative (systemic), Consumer: 300 mg/m<sup>3</sup>

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 5 / 13

DNEL long-term inhalative (local), Consumer: 35,7 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Consumer: 12 mg/m<sup>3</sup>

Reaction mass of ethylbenzene and xylene

EC No. 905-588-0

DNEL long-term dermal (systemic), Workers: 180 mg/kg  
DNEL acute inhalative (local), Workers: 289 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Workers: 442 mg/m<sup>3</sup>  
DNEL long-term inhalative (local), Workers: 221 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 211 mg/m<sup>3</sup>  
DNEL long-term dermal (systemic), Consumer: 108 mg/kg  
DNEL acute inhalative (local), Consumer: 260 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Consumer: 260 mg/m<sup>3</sup>  
DNEL long-term inhalative (local), Consumer: 65,3 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Consumer: 14,8 mg/m<sup>3</sup>

**PNEC:**

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/L  
PNEC aquatic, marine water: 1 mg/L  
PNEC aquatic, intermittent release: 100 mg/L  
PNEC sediment, freshwater: 52,3 mg/kg  
PNEC sediment, marine water: 5,2 mg/kg  
PNEC, soil: 4,59 mg/kg  
PNEC sewage treatment plant (STP): 100 mg/L

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

PNEC aquatic, freshwater: 55,8 mg/L  
PNEC aquatic, marine water: 55,8 mg/L  
PNEC aquatic, intermittent release: 55,8 mg/L  
PNEC sediment, freshwater: 284,7 mg/kg  
PNEC sediment, marine water: 284,7 mg/kg  
PNEC, soil: 22,5 mg/kg  
PNEC sewage treatment plant (STP): 709 mg/L

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

PNEC aquatic, freshwater: 0,18 mg/L  
PNEC aquatic, marine water: 0,018 mg/L  
PNEC aquatic, intermittent release: 0,36 mg/L  
PNEC sediment, freshwater: 0,981 mg/kg  
PNEC sediment, marine water: 0,0981 mg/kg  
PNEC, soil: 0,0903 mg/kg

Reaction mass of ethylbenzene and xylene

EC No. 905-588-0

PNEC aquatic, freshwater: 0,327 mg/L  
PNEC aquatic, marine water: 0,327 mg/L  
PNEC sediment, freshwater: 12,46 mg/kg  
PNEC sediment, marine water: 12,46 mg/kg  
PNEC, soil: 2,31 mg/kg  
PNEC sewage treatment plant (STP): 6,58 mg/L

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Personal protection equipment**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)  
Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 6 / 13

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

**Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties \*

**Appearance:**

**Physical state:** Liquid  
**Colour:** refer to label

**Odour:** Preparations containing solvent

**Odour threshold:** not determined

**pH at 20 °C:** N.A.

**Melting point/freezing point:** n.a.

**Initial boiling point and boiling range:** 80 °C  
Method: calculated.  
Source: butanone

**Flash point:** 16 °C  
Method: calculated.

**Evaporation rate:** not determined

**flammability**

**Burning time:** not determined

**Upper/lower flammability or explosive limits:**

**Lower explosion limit:** 1,36 Vol-%  
Method: calculated.

**Upper explosion limit:** 13,7 Vol-%  
Method: calculated.  
Source: 1-methoxy-2-propanol

**Vapour pressure at 20 °C:** 12,7774 mbar  
Method: calculated.

**Vapour density:** not determined

**Relative density:**

**Density at 20 °C:** 0,84 g/cm<sup>3</sup>  
Method: calculated.

**Solubility(ies):**

**Water solubility at 20 °C:** partially soluble

**Partition coefficient: n-octanol/water:** see section 12

**Auto-ignition temperature:** not determined

**Decomposition temperature:** not determined

**Viscosity at 20 °C:** 100 s 3 mm  
Method: EN ISO 2431

**Explosive properties:** not determined

**Oxidising properties:** not determined

9.2. Other information

**Solid content:** 41,15 weight-%



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 7 / 13

**solvent content:**

**Organic solvents:** 59 weight-%  
**Water:** 0 weight-%

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

**10.3. Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**10.4. Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

not applicable

**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

**11.1. Information on toxicological effects**

\*

**Acute toxicity**

2-methoxy-1-methylethyl acetate

oral, LD50, Rat: 8532 mg/kg

dermal, LD50, Rabbit: > 5000 mg/kg

Based on available data, the classification criteria are not met.

1-methoxy-2-propanol

oral, LD50, Rat: 4016 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (vapours), LC50, Rat: > 25,8 mg/L (4 h)

Based on available data, the classification criteria are not met.

butanone

oral, LD50, Rat: > 2193 mg/kg

Method: OECD 423

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: 34 mg/L (4 h)

Based on available data, the classification criteria are not met.

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg

Method: OECD 423

dermal, LD50, Rabbit: > 14112 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: 23,4 mg/L (4 h)

Method: OECD 403

Based on available data, the classification criteria are not met.

Reaction mass of ethylbenzene and xylene

oral, LD50, Rat: 3523 - 400 mg/kg

dermal, LD50, Rabbit: 12126 mg/kg

inhalative (vapours), LC50, Rat: 21,7 mg/L (4 h)

Harmful in contact with skin or if inhaled.

**Skin corrosion/irritation; Serious eye damage/eye irritation**

butanone

eyes, Rabbit

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 8 / 13

Method: OECD 405  
Causes serious eye irritation.

Reaction mass of ethylbenzene and xylene

Skin (4 h)

Irritating to skin.; Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).; Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

eyes

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

#### **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure; STOT-repeated exposure**

May cause drowsiness or dizziness.

2-methoxy-1-methylethyl acetate

Specific target organ toxicity (single exposure), drowsiness Evaluation May cause drowsiness or dizziness.

1-methoxy-2-propanol

Specific target organ toxicity (single exposure), drowsiness

May cause drowsiness or dizziness.

butanone

Specific target organ toxicity (single exposure), drowsiness

May cause drowsiness or dizziness.

n-butyl acetate

Specific target organ toxicity (single exposure), drowsiness

May cause drowsiness or dizziness.

Reaction mass of ethylbenzene and xylene

Specific target organ toxicity (single exposure), Irritation

May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration hazard**

Reaction mass of ethylbenzene and xylene

Aspiration hazard

May be fatal if swallowed and enters airways.

#### **Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

### **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

#### **12.1. Toxicity**

2-methoxy-1-methylethyl acetate

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 134 mg/L 0 - 180 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 500 mg/L (48 h)

Based on available data, the classification criteria are not met.

1-methoxy-2-propanol

\*



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 9 / 13

Fish toxicity, LC50, *Leuciscus idus* (golden orfe): 6812 mg/L (96 h)  
Based on available data, the classification criteria are not met.  
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea) 21100 - 25900 mg/L (48 h)  
Based on available data, the classification criteria are not met.  
Algae toxicity, ErC50, *Pseudokirchneriella subcapitata*: > 1000 mg/L (168 h); Evaluation Inhibition of growth rate.  
Method: OECD 201

**butanone**

Fish toxicity, LC50, *Pimephales promelas* (fathead minnow): 2990 mg/L (96 h)  
Method: OECD 203  
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 308 mg/L (48 h)  
Method: OECD 202  
Algae toxicity, ErC50, *Pseudokirchneriella subcapitata*: 1972 mg/L (72 h)  
Method: OECD 201  
Bacteria toxicity, EC0, *Pseudomonas putida*: 1150 mg/L (16 h)  
Based on available data, the classification criteria are not met.

**n-butyl acetate**

Fish toxicity, LC50, *Pimephales promelas* (fathead minnow): 18 mg/L (96 h)  
Method: OECD 203  
Daphnia toxicity, EC50, *Daphnia magna* (Big water flea): 44 mg/L (48 h)  
Method: OECD 202  
Algae toxicity, EC50, *Desmodesmus subspicatus*: 397 mg/L (72 h)  
Method: OECD 201  
Based on available data, the classification criteria are not met.

**Reaction mass of ethylbenzene and xylene**

Fish toxicity, LC50, *Oncorhynchus mykiss* (Rainbow trout): 2,6 mg/L (96 h)  
Method: OECD 203  
Daphnia toxicity, LC50, *Daphnia magna* (Big water flea): 1 mg/L (24 h)  
Method: OECD 202  
Algae toxicity, EC50, *Selenastrum capricornutum*: 2,2 mg/L (73 h)  
Method: OECD 201  
Bacteria toxicity, NOEC, Activated sludge: 16 mg/L (28 d)  
Method: OECD 301F  
Based on available data, the classification criteria are not met.

**Long-term Ecotoxicity**

**1-methoxy-2-propanol**

Algae toxicity, ErC50, *Pseudokirchneriella subcapitata*: > 1000 mg/L (168 h)  
Based on available data, the classification criteria are not met.

**Reaction mass of ethylbenzene and xylene**

Fish toxicity, NOEC, *Oncorhynchus mykiss* (Rainbow trout): > 1,3 mg/L (56 D)  
Daphnia toxicity, NOEC, *Ceriodaphnia spec*: 1,17 mg/L (7 D)  
Based on available data, the classification criteria are not met.

**12.2. Persistence and degradability**

**2-methoxy-1-methylethyl acetate**

Biodegradation: 100 % (8 D)  
Readily biodegradable (according to OECD criteria).

**1-methoxy-2-propanol**

Biodegradation: 96 % (28 d)  
Method: OECD 301E  
Readily biodegradable (according to OECD criteria).

**butanone**

Biodegradation: 98 % (28 d)  
Readily biodegradable (according to OECD criteria).

**n-butyl acetate**

Biodegradation, aerobic: 83 % (28 D)  
Method: OECD 301D  
Readily biodegradable (according to OECD criteria).

**Reaction mass of ethylbenzene and xylene**

Biodegradation: 90 % (28 d)

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 10 / 13

Method: OECD 301F  
Readily biodegradable (according to OECD criteria).

**12.3. Bioaccumulative potential**

2-methoxy-1-methylethyl acetate

Partition coefficient: n-octanol/water: 1,2

Method: Log KOW

1-methoxy-2-propanol

Partition coefficient: n-octanol/water: 0,37

butanone

Partition coefficient: n-octanol/water: 0,3

n-butyl acetate

Partition coefficient: n-octanol/water: 2,3

Method: OECD 117

Reaction mass of ethylbenzene and xylene

Partition coefficient: n-octanol/water: 3,12 - 3,2

Method: Log KOW

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

**Bioconcentration factor (BCF)**

Reaction mass of ethylbenzene and xylene

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 25,9

No indication of bioaccumulation potential.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product**

**Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

Land transport (ADR/RID):

Paint

Sea transport (IMDG):

PAINT

Air transport (ICAO-TI / IATA-DGR):

Paint

**14.3. Transport hazard class(es)**

3

**14.4. Packing group**

II

**14.5. Environmental hazards**

Land transport (ADR/RID)

No further relevant information available.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 11 / 13

Marine pollutant

No further relevant information available.

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code D/E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

Maximum VOC content (g/L) of the product in a ready to use condition: 649

**Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**

VOC product category: (Cat. B/e) ; VOC limit value: 840 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 649

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Substance/product listed in the following inventories:**

DSL listed

TSCA listed

**REACH candidate list of substances of very high concern (SVHC) for the approval process.**

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is eligible for inclusion in Annex XIV (list of substances subject to authorization) in accordance with Article 57 in conjunction with Article 59 of REACH.

**Regulation (EC) 1907/2006. material in question applies.Regulation (EC) 1907/2006 (REACH) Annex XIV (list of substances subject to authorization)**

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is considered to be a substance that requires authorization according to REACH Regulation (EC) 1907/2006 Annex XIV.

**15.2. Chemical Safety Assessment**

**For the following substances of this mixture a chemical safety assessment has been carried out:**

\*

EC No. CAS No.	Designation	REACH No.
203-539-1 107-98-2	1-methoxy-2-propanol	01-2119457435-35-xxxx
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29-xxxx
203-603-9 108-65-6	2-methoxy-1-methylethyl acetate	01-2119475791-29-xxxx
201-159-0 78-93-3	butanone	01-2119457290-43-xxxx
905-588-0	Reaction mass of ethylbenzene and xylene	01-2119488216-32-xxxx

**SECTION 16: Other information**

\*

**Full text of classification in section 3**

Flam. Liq. 3 / H226

Flammable liquids

Flammable liquid and vapour.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 12 / 13

STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.

**Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
STOT SE 3	STOT-single exposure	Calculation method.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

You can also find current SDSs for our standard products online on our homepage under **Downloads** in the relevant product area.

\* Data changed compared with the previous version

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830

Article No.: 243X46  
Print date: 17.09.2021  
Version: 4.2

PREMIUM Window Pen  
Revision date: 17.09.2021  
Issue date: 17.09.2021

53361 GB  
Page 13 / 13

