

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546 King Acrylic Covering Lacquer WB L  
Print date: 08.07.2019 Revision date: 05.07.2019 53361 EN  
Version: 3.19 Issue date: 05.07.2019 Page 1 / 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. **product identifiers**

Article No. (manufacturer/supplier) 248546  
Trade name/designation King Acrylic Covering Lacquer WB L

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

Coating (Paint, Varnish).

**Uses advised against:**

Do not use for products which come into contact with the food stuffs.

1.3. **Details of the supplier of the safety data sheet**

**Manufacturer/supplier**

Heinrich König & Co.KG  
An der Rosenhelle 5  
D-61138 Niederdorfelden

Telephone: +49 6101 5360 0  
Telefax: +49 6101 5360 11

**Dept. responsible for information:**

Laboratory

Telephone: +49 6101 5360 71

Only available during office hours:

Mon - Thurs 08:00 to 16:00  
Friday 08:00 - 12:30

E-mail (competent person)

SDB@heinrich-koenig.de

1.4. **Emergency telephone number**

Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK  
GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification**

2.1. **Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

STOT SE 3 / H336

STOT-single exposure

May cause drowsiness or dizziness.

2.2. **Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Danger**

**Hazard statements**

H225

Highly flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

**Precautionary statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370 + P378

In case of fire: Use foam to extinguish.

**Hazard components for labelling**

1-methoxy-2-propanol

**Supplemental Hazard information (EU)**

EUH066

Repeated exposure may cause skin dryness or cracking.

2.3. **Other hazards**

No information available.

**SECTION 3: Composition / information on ingredients**

3.2. **Mixtures**

**Description** Acrylic resin lacquer

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546  
Print date: 08.07.2019  
Version: 3.19

King Acrylic Covering Lacquer WB L  
Revision date: 05.07.2019  
Issue date: 05.07.2019

53361 EN  
Page 2 / 12

EC No. CAS No. INDEX No.	REACH No. Designation classification // Remark	Wt %
203-539-1 107-98-2 603-064-00-3	01-2119457435-35-xxxx 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	20 < 25
204-658-1 123-86-4 607-025-00-1	01-2119485493-29-xxxx n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	10 < 20
203-603-9 108-65-6 607-195-00-7	01-2119475791-29-xxxx 2-methoxy-1-methylethyl acetate Flam. Liq. 3 H226	7 < 10
201-159-0 78-93-3 606-002-00-3	01-2119457290-43-xxxx butanone Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	5 < 7
215-535-7 1330-20-7 601-022-00-9	01-2119488216-32-xxxx xylene, mixture of isomers Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226	2,5 < 3

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546  
Print date: 08.07.2019  
Version: 3.19

King Acrylic Covering Lacquer WB L  
Revision date: 05.07.2019  
Issue date: 05.07.2019

53361 EN  
Page 3 / 12

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

TWA: 375 mg/m<sup>3</sup>; 100 ppm

STEL: 560 mg/m<sup>3</sup>; 150 ppm

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

TWA: 724 mg/m<sup>3</sup>; 150 ppm

STEL: 966 mg/m<sup>3</sup>; 200 ppm

2-methoxy-1-methylethyl acetate

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546 King Acrylic Covering Lacquer WB L  
Print date: 08.07.2019 Revision date: 05.07.2019  
Version: 3.19 Issue date: 05.07.2019

53361 EN  
Page 4 / 12

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

TWA: 274 mg/m<sup>3</sup>; 50 ppm

STEL: 548 mg/m<sup>3</sup>; 100 ppm

butanone

INDEX No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

TWA: 600 mg/m<sup>3</sup>; 200 ppm

STEL: 899 mg/m<sup>3</sup>; 300 ppm

xylene, mixture of isomers

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

TWA: 441 mg/m<sup>3</sup>; 100 ppm

STEL: 662 mg/m<sup>3</sup>; 150 ppm

**Additional information**

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

**DNEL:**

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 50,6 mg/kg

DNEL acute inhalative (local), Workers: 553,5 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 369 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 3,3 mg/kg

DNEL long-term dermal (systemic), Consumer: 18,1 mg/kg

DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m<sup>3</sup>

butanone

INDEX No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

DNEL long-term dermal (systemic), Workers: 1161 mg/kg

DNEL long-term inhalative (systemic), Workers: 600 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 31 mg/kg

DNEL acute dermal, short-term (local), Consumer: 412 mg/kg

DNEL long-term dermal (systemic), Consumer: 206 mg/kg

DNEL long-term inhalative (systemic), Consumer: 106 mg/m<sup>3</sup>

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute dermal, short-term (systemic), Workers: 11 mg/kg

DNEL long-term dermal (systemic), Workers: 7 mg/kg

DNEL acute inhalative (local), Workers: 600 mg/m<sup>3</sup>

DNEL acute inhalative (systemic), Workers: 600 mg/m<sup>3</sup>

DNEL long-term inhalative (local), Workers: 300 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 48 mg/m<sup>3</sup>

DNEL short-term oral (acute), Consumer: 2 mg/kg

DNEL long-term oral (repeated), Consumer: 2 mg/kg

DNEL acute dermal, short-term (systemic), Consumer: 6 mg/kg

DNEL long-term dermal (systemic), Consumer: 3,4 mg/kg

DNEL acute inhalative (local), Consumer: 300 mg/m<sup>3</sup>

DNEL acute inhalative (systemic), Consumer: 300 mg/m<sup>3</sup>

DNEL long-term inhalative (local), Consumer: 35,7 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Consumer: 12 mg/m<sup>3</sup>

xylene, mixture of isomers

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 180 mg/kg

DNEL acute inhalative (local), Workers: 289 mg/m<sup>3</sup>

DNEL acute inhalative (systemic), Workers: 289 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 77 mg/m<sup>3</sup>

DNEL long-term dermal (systemic), Consumer: 108 mg/kg

DNEL acute inhalative (local), Consumer: 174 mg/m<sup>3</sup>

DNEL acute inhalative (systemic), Consumer: 174 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Consumer: 14,8 mg/m<sup>3</sup>

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546 King Acrylic Covering Lacquer WB L  
Print date: 08.07.2019 Revision date: 05.07.2019  
Version: 3.19 Issue date: 05.07.2019

53361 EN  
Page 5 / 12

**PNEC:**

1-methoxy-2-propanol  
INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2  
PNEC aquatic, freshwater: 10 mg/l  
PNEC sediment, freshwater: 41,6 mg/kg  
PNEC sediment, marine water: 4,17 mg/kg  
PNEC, soil: 2,47 mg/kg

butanone  
INDEX No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3  
PNEC aquatic, freshwater: 55,8 mg/l  
PNEC aquatic, marine water: 55,8 mg/l  
PNEC aquatic, intermittent release: 55,8 mg/l  
PNEC sediment, freshwater: 284,7 mg/kg  
PNEC sediment, marine water: 284,7 mg/kg  
PNEC, soil: 22,5 mg/kg  
PNEC sewage treatment plant (STP): 709 mg/l

n-butyl acetate  
INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4  
PNEC aquatic, freshwater: 0,18 mg/l  
PNEC aquatic, marine water: 0,018 mg/l  
PNEC aquatic, intermittent release: 0,36 mg/l  
PNEC sediment, freshwater: 0,981 mg/kg  
PNEC sediment, marine water: 0,0981 mg/kg  
PNEC, soil: 0,0903 mg/kg

xylene, mixture of isomers  
INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7  
PNEC aquatic, freshwater: 0,327 mg/l  
PNEC aquatic, marine water: 0,327 mg/l  
PNEC aquatic, intermittent release: 0,327 mg/l  
PNEC sediment, freshwater: 12,46 mg/kg  
PNEC sediment, marine water: 12,46 mg/kg  
PNEC, soil: 2,31 mg/kg  
PNEC sewage treatment plant (STP): 6,58 mg/l

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Personal protection equipment**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

**Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546  
Print date: 08.07.2019  
Version: 3.19

King Acrylic Covering Lacquer WB L  
Revision date: 05.07.2019  
Issue date: 05.07.2019

53361 EN  
Page 6 / 12

9.1. Information on basic physical and chemical properties \*

<b>Appearance:</b>	
<b>Physical state:</b>	<b>Liquid</b>
<b>Colour:</b>	<b>refer to label</b>
<b>Odour:</b>	<b>Preparations containing solvent</b>
<b>Odour threshold:</b>	<b>not determined</b>
<b>pH at 20 °C:</b>	<b>N.A.</b>
<b>Melting point/freezing point:</b>	<b>n.a.</b>
<b>Initial boiling point and boiling range:</b>	<b>80 °C</b> Method: calculated. Source: butanone
<b>Flash point:</b>	<b>16 °C</b> Method: calculated.
<b>Evaporation rate:</b>	<b>not determined</b>
<b>flammability</b>	
<b>Burning time (s):</b>	<b>not determined</b>
<b>Upper/lower flammability or explosive limits:</b>	
<b>Lower explosion limit:</b>	<b>1,36 Vol-%</b> Method: calculated.
<b>Upper explosion limit:</b>	<b>13,7 Vol-%</b> Method: calculated. Source: 1-methoxy-2-propanol
<b>Vapour pressure at 20 °C:</b>	<b>12,7782 mbar</b> Method: calculated.
<b>Vapour density:</b>	<b>not determined</b>
<b>Relative density:</b>	
<b>Density at 20 °C:</b>	<b>0,84 g/cm<sup>3</sup></b> Method: calculated.
<b>Solubility(ies):</b>	
<b>Water solubility (g/L) at 20 °C:</b>	<b>partially soluble</b>
<b>Partition coefficient: n-octanol/water:</b>	<b>see section 12</b>
<b>Auto-ignition temperature:</b>	<b>not determined</b>
<b>Decomposition temperature:</b>	<b>not determined</b>
<b>Viscosity at 20 °C:</b>	<b>100 s 3 mm</b> Method: EN ISO 2431
<b>Explosive properties:</b>	<b>not determined</b>
<b>Oxidising properties:</b>	<b>not determined</b>

9.2. Other information \*

<b>Solid content (%):</b>	<b>41,15 Wt %</b>
<b>solvent content:</b>	
<b>Organic solvents:</b>	<b>59 Wt %</b>
<b>Water:</b>	<b>0 Wt %</b>

**SECTION 10: Stability and reactivity**

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546 King Acrylic Covering Lacquer WB L  
Print date: 08.07.2019 Revision date: 05.07.2019  
Version: 3.19 Issue date: 05.07.2019

53361 EN  
Page 7 / 12

Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

not applicable

**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

**11.1. Information on toxicological effects**

**Acute toxicity**

2-methoxy-1-methylethyl acetate

oral, LD50, Rat: 8532 mg/kg

dermal, LD50, Rabbit: > 5000 mg/kg

Based on available data, the classification criteria are not met.

1-methoxy-2-propanol

oral, LD50, Rat: 5000 mg/kg

dermal, LD50, Rabbit: 13500 mg/kg

inhalative (vapours), LC50, Rat: > 20 mg/l (4 h)

Based on available data, the classification criteria are not met.

butanone

oral, LD50, Rat: > 2193 mg/kg

Method: OECD 423

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: 34 mg/l (4 h)

Based on available data, the classification criteria are not met.

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg

Method: OECD 423

dermal, LD50, Rabbit: > 14112 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: 23,4 mg/l (4 h)

Method: OECD 403

Based on available data, the classification criteria are not met.

xylene, mixture of isomers

oral, LD50, Rat: > 2000 mg/kg

dermal, LD50, Rabbit: > 1700 mg/kg

inhalative (vapours), LC50, Rat: > 21,7 mg/l (4 h)

Harmful in contact with skin or if inhaled.

**Skin corrosion/irritation; Serious eye damage/eye irritation**

butanone

eyes, Rabbit

Method: OECD 405

Causes serious eye irritation.

xylene, mixture of isomers

Skin (4 h)

Irritating to skin.; Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).; Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

eyes

Causes serious eye irritation.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546 King Acrylic Covering Lacquer WB L  
Print date: 08.07.2019 Revision date: 05.07.2019  
Version: 3.19 Issue date: 05.07.2019

53361 EN  
Page 8 / 12

**STOT-single exposure; STOT-repeated exposure**

May cause drowsiness or dizziness.

1-methoxy-2-propanol

Specific target organ toxicity (single exposure), drowsiness  
May cause drowsiness or dizziness.

butanone

Specific target organ toxicity (single exposure), drowsiness  
May cause drowsiness or dizziness.

n-butyl acetate

Specific target organ toxicity (single exposure), drowsiness  
May cause drowsiness or dizziness.

xylene, mixture of isomers

Specific target organ toxicity (single exposure), Irritation  
May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

xylene, mixture of isomers

Aspiration hazard

May be fatal if swallowed and enters airways.

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

**12.1. Toxicity**

2-methoxy-1-methylethyl acetate

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 134 mg/l 0 - 180 mg/l (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 500 mg/l (48 h)

Based on available data, the classification criteria are not met.

1-methoxy-2-propanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 6812 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea) 21100 - 25900 mg/l (48 h)

Based on available data, the classification criteria are not met.

butanone

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 2990 mg/l (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 308 mg/l (48 h)

Method: OECD 202

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 1972 mg/l (72 h)

Method: OECD 201

Bacteria toxicity, EC0, Pseudomonas putida: 1150 mg/l (16 h)

Based on available data, the classification criteria are not met.

n-butyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 18 mg/l (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 44 mg/l (48 h)



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546 King Acrylic Covering Lacquer WB L  
Print date: 08.07.2019 Revision date: 05.07.2019  
Version: 3.19 Issue date: 05.07.2019

53361 EN  
Page 9 / 12

Method: OECD 202  
Algae toxicity, EC50, *Desmodesmus subspicatus*: 397 mg/l (72 h)  
Method: OECD 201  
Based on available data, the classification criteria are not met.

xylene, mixture of isomers

Fish toxicity, LC50, *Oncorhynchus mykiss* (Rainbow trout): 2,6 mg/l (96 h)  
Method: OECD 203  
Daphnia toxicity, IC50, *Daphnia magna* (Big water flea): 1 mg/l (24 h)  
Method: OECD 202  
Algae toxicity, EC50, *Pseudokirchneriella subcapitata*: 2,2 mg/l (72 h)  
Method: OECD 201  
Algae toxicity, NOEC, *Pseudokirchneriella subcapitata*: 0,44 mg/l (72 h)  
Method: OECD 201  
Bacteria toxicity, NOEC, Activated sludge: 157 mg/l (3 h)  
Method: OECD 209  
Based on available data, the classification criteria are not met.

#### Long-term Ecotoxicity

1-methoxy-2-propanol

Algae toxicity, ErC50, *Pseudokirchneriella subcapitata*: > 1000 mg/l (168 h)  
Based on available data, the classification criteria are not met.

xylene, mixture of isomers

Fish toxicity, NOEC, *Oncorhynchus mykiss* (Rainbow trout): > 1,3 mg/l (56 D)  
Daphnia toxicity, NOEC, *Ceriodaphnia spec*: 1,17 mg/l (7 D)  
Based on available data, the classification criteria are not met.

#### 12.2. Persistence and degradability

2-methoxy-1-methylethyl acetate

Biodegradation: 100 % (8 D)  
Readily biodegradable (according to OECD criteria).

1-methoxy-2-propanol

Biodegradation: > 70 %  
Method: DOC reduction.  
Readily biodegradable (according to OECD criteria).

butanone

Biodegradation: 98 % (28 d)  
Readily biodegradable (according to OECD criteria).

n-butyl acetate

Biodegradation, aerobic: 83 % (28 D)  
Method: OECD 301D  
Readily biodegradable (according to OECD criteria).

xylene, mixture of isomers

Biodegradation:  
Readily biodegradable (according to OECD criteria).

#### 12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate

Partition coefficient: n-octanol/water: 1,2  
Method: Log KOC

1-methoxy-2-propanol

Partition coefficient: n-octanol/water: 0,43

butanone

Partition coefficient: n-octanol/water: 0,3

n-butyl acetate

Partition coefficient: n-octanol/water: 2,3  
Method: OECD 117

xylene, mixture of isomers

Partition coefficient: n-octanol/water: 2,77

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546 King Acrylic Covering Lacquer WB L  
Print date: 08.07.2019 Revision date: 05.07.2019  
Version: 3.19 Issue date: 05.07.2019

53361 EN  
Page 10 / 12

**Bioconcentration factor (BCF)**

xylene, mixture of isomers

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 25,9

No indication of bioaccumulation potential.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

Land transport (ADR/RID):

Paint

Sea transport (IMDG):

PAINT

Air transport (ICAO-TI / IATA-DGR):

Paint

**14.3. Transport hazard class(es)**

3

**14.4. Packing group**

II

**14.5. Environmental hazards**

Land transport (ADR/RID)

No further relevant information available.

Marine pollutant

No further relevant information available.

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code

D/E

SPECIAL PROVISIONS 640D

**Sea transport (IMDG)**

EmS-No.

F-E, S-E

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546  
Print date: 08.07.2019  
Version: 3.19

King Acrylic Covering Lacquer WB L  
Revision date: 05.07.2019  
Issue date: 05.07.2019

53361 EN  
Page 11 / 12

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions**

VOC-value (in g/L): 649,019

**Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**

VOC product category: (Cat. B/e) ; VOC limit value: 840 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 649,019

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**15.2. Chemical Safety Assessment**

**For the following substances of this mixture a chemical safety assessment has been carried out:**

EC No. CAS No.	Designation	REACH No.
203-539-1 107-98-2	1-methoxy-2-propanol	01-2119457435-35-xxxx
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29-xxxx
203-603-9 108-65-6	2-methoxy-1-methylethyl acetate	01-2119475791-29-xxxx
201-159-0 78-93-3	butanone	01-2119457290-43-xxxx
215-535-7 1330-20-7	xylene, mixture of isomers	01-2119488216-32-xxxx

**SECTION 16: Other information**

**Full text of classification in section 3**

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.

**Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
STOT SE 3	STOT-single exposure	Calculation method.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 248546 King Acrylic Covering Lacquer WB L  
Print date: 08.07.2019 Revision date: 05.07.2019 53361 EN  
Version: 3.19 Issue date: 05.07.2019 Page 12 / 12

---

EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

\* Data changed compared with the previous version