

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 1 / 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **product identifiers**

Article No. (manufacturer/supplier) A34X00
Trade name/designation AQUA Clear Lacquer
Art.no. A34200, A34300, A34400; A34500, A34600

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses:

Coating (Paint, Varnish).

Uses advised against:

Do not use for products which come into contact with the food stuffs.

1.3. **Details of the supplier of the safety data sheet**

Manufacturer/supplier

Heinrich König GmbH & Co.KG
An der Rosenhelle 5
D-61138 Niederdorfelden

Telephone: +49 6101 5360 0
Telefax: +49 6101 5360 11
E-mail: Info@heinrich-koenig.de
Website: www.heinrich-koenig.de

Department responsible for information:

Laboratory

Only available during office hours:

Telephone: +49 6101 5360 71
Mon - Thurs 08:00 to 16:00
Friday 08:00 - 12:30

E-mail (competent person)

SDB@heinrich-koenig.de

1.4. **Emergency telephone number**

Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK
GmbH +49 (0)6132-84463

Ireland (Éireann)

Emergency medical information: 8am-10pm (seven days)
contact National Poisons Information Centre, Beaumont
Hospital, Dublin 9 DOV2NO, Ireland.
Telephone Number: "+353 (0)1 809 2166 "

SECTION 2: Hazards identification

2.1. **Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Aerosol 1 / H222

Aerosol

Extremely flammable aerosol.

Aerosol 1 / H229

Aerosol

Pressurised container: May burst if heated.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

2.2. **Label elements**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Do not pierce or burn, even after use.

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Hazard components for labelling

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 2 / 11

No further relevant information available.

Supplemental hazard information

No further relevant information available.

2.3. **Other hazards**

No information available.

SECTION 3: Composition / information on ingredients

3.2. **Mixtures**

Description Aerosol

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
204-065-8 115-10-6	01-2119472128-37-xxxx dimethyl ether	25 < 50
603-019-00-8 200-661-7 67-63-0	Flam. Gas 1 H220 / liquefied gas H280 01-2119457558-25-xxxx propan-2-ol	10 < 20
603-117-00-0 200-578-6 64-17-5	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 01-2119457610-43-xxxx Ethanol	10 < 20
603-002-00-5	Flam. Liq. 2 H225 Specific concentration limit (SCL): Eye Irrit. 2 H319 >= 50	
215-647-6 1336-21-6	01-2119982985-14-xxxx ammonia	0,3 < 1
007-001-01-2	Skin Corr. 1B H314 / Eye Dam. 1 H318 / STOT SE 3 H335 / Aquatic Acute 1 H400 / Aquatic Chronic 2 H411	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 3 / 11

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIV). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Occupational exposure limit values:

dimethyl ether

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 4 / 11

Index No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

TWA: 766 mg/m³; 400 ppm

STEL: 958 mg/m³; 500 ppm

propan-2-ol

Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

TWA: 999 mg/m³; 400 ppm

STEL: 1250 mg/m³; 500 ppm

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

TWA: 1920 mg/m³; 1000 ppm

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

dimethyl ether

Index No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

DNEL long-term inhalative (systemic), Workers: 1894 mg/m³

DNEL long-term inhalative (systemic), Consumer: 471 mg/m³

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

DNEL long-term dermal (systemic), Workers: 343 mg/kg

DNEL acute inhalative (local), Workers: 1900 mg/m³

DNEL long-term inhalative (systemic), Workers: 950 mg/m³

DNEL long-term oral (repeated), Consumer: 87 mg/kg

DNEL acute dermal, short-term (systemic), Consumer: 950 mg/kg

DNEL long-term dermal (systemic), Consumer: 206 mg/kg

DNEL acute inhalative (local), Consumer: 950 mg/m³

DNEL long-term inhalative (systemic), Consumer: 114 mg/m³

propan-2-ol

Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

DNEL long-term dermal (systemic), Workers: 888 mg/kg

DNEL long-term inhalative (systemic), Workers: 500 mg/m³

DNEL long-term oral (repeated), Consumer: 26 mg/kg

DNEL long-term dermal (systemic), Consumer: 319 mg/kg

DNEL long-term inhalative (systemic), Consumer: 89 mg/m³

ammonia

Index No. 007-001-01-2 / EC No. 215-647-6 / CAS No. 1336-21-6

DNEL short-term oral (acute), Workers:

DNEL acute dermal, short-term (systemic), Workers: 6,8 mg/kg

DNEL long-term dermal (systemic), Workers: 6,8 mg/kg

DNEL long-term inhalative (systemic), Workers: 47,6 mg/m³

PNEC:

dimethyl ether

Index No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

PNEC aquatic, freshwater: 0,155 mg/L

PNEC sediment, freshwater: 0,681 mg/kg

PNEC, soil: 0,045 mg/kg

PNEC sewage treatment plant (STP): 160 mg/L

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

PNEC aquatic, freshwater: 0,96 mg/L

PNEC aquatic, marine water: 0,79 mg/L

PNEC aquatic, intermittent release: 2,75 mg/L

PNEC sediment, freshwater: 3,6 mg/kg

PNEC sediment, marine water: 2,9 mg/kg

PNEC, soil: 0,63 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 5 / 11

PNEC sewage treatment plant (STP): 580 mg/L
PNEC Secondary Poisoning: 0,72 mg/kg

propan-2-ol

Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

PNEC aquatic, freshwater: 140,9 mg/L
PNEC aquatic, marine water: 140,9 mg/L
PNEC aquatic, intermittent release: 140,9 mg/L
PNEC sediment, freshwater: 552 mg/kg
PNEC sediment, marine water: 552 mg/kg
PNEC, soil: 28 mg/kg
PNEC sewage treatment plant (STP): 2251 mg/L
PNEC Secondary Poisoning: 160 mg/kg

ammonia

Index No. 007-001-01-2 / EC No. 215-647-6 / CAS No. 1336-21-6

PNEC aquatic, freshwater: 0,0011 mg/L
PNEC aquatic, intermittent release: 0,0068 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Colour: colourless

Odour: Preparations containing solvent

Odour threshold: not determined

pH at 20 °C: N.A.

Melting point/freezing point: n.a.

Initial boiling point and boiling range: -24 °C
Method: calculated.
Source: dimethyl ether

Flash point: -41 °C
Method: calculated.

Evaporation rate: not determined

flammability

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 6 / 11

Burning time:	not determined
Upper/lower flammability or explosive limits:	
Lower explosion limit:	2,76 Vol-% Method: calculated.
Upper explosion limit:	33 Vol-% Method: calculated. Source: ammonia
Vapour pressure at 20 °C:	3664,4814 mbar Method: calculated.
Vapour density:	not determined
Relative density:	
Density at 20 °C:	0,79 g/cm³ Method: calculated.
Solubility(ies):	
Water solubility at 20 °C:	partially soluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
Viscosity at 20 °C:	12 s 4 mm Method: DIN 53211
Explosive properties:	not determined
Oxidising properties:	not determined
9.2. Other information	
Solid content:	8,19 weight-%
solvent content:	
Organic solvents:	74 weight-%
Water:	17 weight-%

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

dimethyl ether

inhalative (Gases), LC50, Rat: > 20000 ppmV (4 h)

Ethanol

oral, LD50, Rat: 10470 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 2000 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 7 / 11

Method: OECD 402
inhalative (vapours), LC50, Rat: 51 mg/L (4 h)
Method: OECD 403
Based on available data, the classification criteria are not met.

propan-2-ol
oral, LD50, Rat: 5840 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: 13900 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: 25 mg/L (4 h); Evaluation OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye irritation.

Ethanol
eyes

propan-2-ol
eyes
Method: OECD 405
Causes serious eye irritation.

ammonia
Skin, Rabbit
Method: OECD 404
Skin corrosion
eyes
Causes serious eye damage.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

dimethyl ether
Specific target organ toxicity (single exposure), drowsiness Evaluation May cause drowsiness or dizziness.
literature value

propan-2-ol
Specific target organ toxicity (single exposure), drowsiness Evaluation central nervous system
May cause drowsiness or dizziness.

ammonia
Specific target organ toxicity (single exposure), Irritation
May cause respiratory irritation.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
Do not allow to enter into surface water or drains.

12.1. **Toxicity**

Ethanol

*

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 8 / 11

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 15300 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 12340 mg/L (48 h)
Algae toxicity, ErC50, Chlorella vulgaris: 275 mg/L (72 h)
Method: OECD 201
Bacteria toxicity, EC50, Pseudomonas putida: 5800 mg/L (4 h)
Based on available data, the classification criteria are not met.

propan-2-ol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 9640 mg/L (96 h)
Method: OECD 203
Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h)
Algae toxicity, ErC50, Scenedesmus subspicatus: > 100 mg/L (72 h)
Based on available data, the classification criteria are not met.

ammonia

Fish toxicity, LC50: 0,89 mg/L (96 h)
Very toxic to aquatic organisms.
Daphnia toxicity, EC50: 101 mg/L (48 h)
Algae toxicity, ErC50: 2700 mg/L (432 h)
Very toxic to aquatic organisms.

Long-term Ecotoxicity

ammonia

Fish toxicity, LC50 (96 h)
Toxic to aquatic life with long lasting effects.
Fish toxicity, NOEC: 0,022 mg/L (73)
Daphnia toxicity, NOEC: 0,79 mg/L (96)

12.2. Persistence and degradability

Ethanol

Biodegradation, aerobic.: 97 % (28 D)
Readily biodegradable (according to OECD criteria).

propan-2-ol

Biodegradation: 53 % (5 D)
Readily biodegradable (according to OECD criteria).

ammonia

Biodegradation:
Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

dimethyl ether

Partition coefficient: n-octanol/water: 0,7
Method: Log KOW

Ethanol

Partition coefficient: n-octanol/water: -0,35

propan-2-ol

Partition coefficient: n-octanol/water: 0,05

ammonia

Partition coefficient: n-octanol/water: -0,64

Bioconcentration factor (BCF)

Ethanol

Bioconcentration factor (BCF): 0,66
No indication of bioaccumulation potential.

12.4. Mobility in soil

propan-2-ol

:
water-soluble

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 9 / 11

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

150110* packaging containing residues of or contaminated by dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1950

14.2. UN proper shipping name

Land transport (ADR/RID):

Aerosols, flammable

Sea transport (IMDG):

AEROSOLS

Air transport (ICAO-TI / IATA-DGR):

Aerosols, flammable

14.3. Transport hazard class(es)

2.1

14.4. Packing group

No further relevant information available.

14.5. Environmental hazards

Land transport (ADR/RID)

No further relevant information available.

Marine pollutant

No further relevant information available.

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

D

Sea transport (IMDG)

EmS-No.

F-D, S-U

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

Maximum VOC content (g/L) of the product in a ready to use condition: 590

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

DSL listed

TSCA listed

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 10 / 11

REACH candidate list of substances of very high concern (SVHC) for the approval process.

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is eligible for inclusion in Annex XIV (list of substances subject to authorization) in accordance with Article 57 in conjunction with Article 59 of REACH.

Regulation (EC) 1907/2006. material in question applies. Regulation (EC) 1907/2006 (REACH) Annex XIV (list of substances subject to authorization)

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is considered to be a substance that requires authorization according to REACH Regulation (EC) 1907/2006 Annex XIV.

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
204-065-8 115-10-6	dimethyl ether	01-2119472128-37-xxxx
200-661-7 67-63-0	propan-2-ol	01-2119457558-25-xxxx
200-578-6 64-17-5	Ethanol	01-2119457610-43-xxxx
215-647-6 1336-21-6	ammonia	01-2119982985-14-xxxx

SECTION 16: Other information

Full text of classification in section 3

Flam. Gas 1 / H220 liquefied gas / H280	flammable gases Gases under pressure	Extremely flammable gas. Contains gas under pressure; may explode if heated.
Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411	Flammable liquids Serious eye damage/eye irritation STOT-single exposure Skin corrosion/irritation Serious eye damage/eye irritation STOT-single exposure Hazardous to the aquatic environment Hazardous to the aquatic environment	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Causes severe skin burns and eye damage. Causes serious eye damage. May cause respiratory irritation. Very toxic to aquatic organisms. Toxic to aquatic life with long lasting effects.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Aerosol 1	Aerosol	On basis of test data.
Aerosol 1	Aerosol	On basis of test data.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: A34X00
Print date: 04.08.2021
Version: 1.29

AQUA Clear Lacquer
Revision date: 10.06.2021
Issue date: 10.06.2021

53361 GB
Page 11 / 11

LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

You can also find current SDSs for our standard products online on our homepage under **Downloads** in the relevant product area.

* Data changed compared with the previous version